

**SUBJECT: HI-HI-2000 HEUI® Injector Flow Correlation**
**Bench Speed: 2,000 RPM**
**Fuel Supply: 60 psi**
**Test Fluid Temperature: 40° C**
**Test Fluid: Viscor 1487 or Benzoil UCF-1 (SAE J967/ISO 4113)**
**Flow correlation developed by Alliant Power – For reference only**

AP part number	Injection pressure (psi)	Pulse width (ms)	Hydraulic injection hi-2000 mm3 per/stroke
AP63800AA	2500	1.5	50-59
	500	1.2	4-12
AP63801AB	2500	1.5	43-54
	600	1.8	8-17
AP63802AC	2500	1.5	53-62
	500	1.2	5-13
AP63803AD	2500	1.7	57-69
	600	1.9	9-18
AP63804AE	2500	1.7	57-69
	600	1.9	9-18
AP63805BA	2500	2.1	113-127
	600	1.3	15-24
AP63806BB	2500	2.1	90-102
	600	1.3	12-21
AP63807BC	2500	2.1	90-103
	600	1.3	14-23
AP63808BD	2500	2.5	151-169
	800	1.0	12-22
AP63809BE	2500	2.6	115-132
	600	2.1	20-30
AP63810BF	2500	2.8	143-161
	700	2.3	32-42
AP63811BI	2500	2.6	86-104
	700	2.3	18-28
AP63812BJ	2500	2.6	108-126
	700	2.3	22-34
AP63813BN	2500	2.8	130-152
	700	2.3	26-39
AP63814BP	2500	2.8	94-116
	700	2.3	18-30

For more information visit

**AlliantPower.com**

Alliant Power Technical Support: 800.735.9775 | techsupport@AlliantPower.com